

200311582-1

RECEIVED  
CENTRAL FAX CENTER  
OCT 19 2007

10/686,896

IN THE CLAIMS:

Please amend the claims as follows:

1. (currently amended) A multi-cell fuel cell layer, comprising:  
a substrate;  
an array of fuel cells each having an anode, a cathode, and an electrolyte disposed on said substrate;  
conductors electrically coupled to said fuel cell array;  
a fuel flow channel defined in a first, ~~[[an]]~~ anode side of said substrate; and  
a cathode air flow channel defined in a second and opposite, cathode side of said substrate.
2. (original) The fuel cell layer of claim 1, further comprising a fuel inlet and an exhaust defined in said substrate.
3. (original) The fuel cell layer of claim 2, wherein said fuel inlet and said exhaust are in fluid communication with said fuel flow channel.
4. (original) The fuel cell layer of claim 2, further comprising a cathode air inlet and an excess cathode air outlet defined in said substrate.
5. (original) The fuel cell layer of claim 4, wherein said cathode air inlet and said excess cathode air outlet are in fluid communication with said cathode air flow channel.

200311582-1

10/686,896

6. (previously presented) The fuel cell layer of claim 4, wherein said fuel inlet and exhaust are defined in first and second opposing corner portions of said substrate and said inlet cathode air and excess cathode air outlets are defined in third and fourth opposing corner portions of said substrate.

7. (previously presented) The fuel cell layer of claim 1, wherein said array of fuel cells are disposed within said fuel flow channel and said cathode air flow channel.

8. (previously presented) The fuel cell layer of claim 4, wherein said conductors comprise a positive conductor extending to said cathode air inlet and a negative conductor extending to said excess cathode air outlet.

9. (original) The fuel cell layer of claim 1, wherein said fuel flow channel is defined along a first axis and said cathode air flow channel is disposed along a second axis disposed at an angle with said first axis.

10. (original) The fuel cell layer of claim 9, wherein said first axis is substantially normal to said second axis.

11. (original) The fuel cell layer of claim 1, wherein said conductors are located on said cathode side of said substrate, said cathode side serving as a circuit side of said substrate.

12. (original) The fuel cell layer of claim 1, wherein said electrolyte seals non-active portions of said substrate.

200311582-1

10/686,896

13. (currently amended) The fuel cell layer of claim 1, further comprising flow modification features associated with either or both of said fuel flow channel and said cathode air flow channel, said flow modification features being configured to distribute a flow ~~of fuel or air emerging from an inlet across a width of said fuel flow channel or said air flow channel, respectively.~~ [[or]]

14. (original) The fuel cell layer of claim 13, wherein said flow modification features comprise a plurality of baffles.

15. (original) The fuel cell layer of claim 1, wherein said conductors are located on said anode side of said substrate, said anode side serving as a circuit side of said fuel cell layer.

16. (currently amended) A fuel cell system, comprising:  
a plurality of fuel cell layers each including an array of fuel cells each having an anode, a cathode, an electrolyte and conductors disposed on a substrate, a fuel flow channel defined in an anode side of said substrate, and a cathode air flow channel defined in [[a]] an opposite,  
cathode side of said substrate,  
wherein said fuel cell layers are alternating stacked.

17. (previously presented) The system of claim 16, wherein said fuel cell layers are coupled such that a fuel cell layer shares a fuel flow channel with a first adjacent fuel cell layer thereby forming a fuel flow plenum.

200311582-1

10/686,896

18. (original) The system of claim 17, wherein said fuel cell layers are coupled such that a fuel cell layer shares a cathode air flow channel with a second adjacent fuel cell layer thereby forming a cathode air flow plenum.

19. (original) The system of claim 18, further comprising fuel inlets and exhausts defined in said substrates.

20. (original) The system of claim 19, wherein a plurality of said fuel inlets form a fuel inlet plenum and a plurality of said exhausts form an exhaust plenum.

21. (original) The system of claim 20, wherein said fuel inlet plenum and said exhaust plenum are in fluid communication with said fuel flow plenums.

22. (original) The system of claim 21, further comprising cathode air inlets and excess cathode air outlets defined in said substrates.

23. (original) The system of claim 22, wherein a plurality of said cathode air inlets form a cathode air inlet plenum and a plurality of said excess cathode air outlets form an excess cathode air outlet plenum.

24. (original) The system of claim 23, wherein said inlet cathode air plenum and said excess cathode air outlet plenum are in fluid communication with said cathode air flow plenums.

200311582-1

10/686,896

25. (previously presented) The system of claim 24, wherein said conductors further comprise a positive conductor on each of said fuel cell layers extending to said cathode air inlets and a negative conductor on each of said fuel cell layers extending to said excess cathode air outlets.

26. (previously presented) The system of claim 25, further comprising a positive stack connection coupled to each of said positive conductors through said inlet cathode air plenum and a negative stack connection coupled to each of said negative conductors through said excess cathode air outlet plenum.

27. (previously presented) The system of claim 26, wherein fuel inlets and exhausts are defined in first and second opposing corner portions of said substrates and said inlet cathode air inlets and excess cathode air outlets are defined in third and fourth opposing corner portions of said substrates.

28. (previously presented) The system of claim 27, wherein said inlets comprise ports that can be opened or closed to selectively activate or deactivate each individual layer of said plurality of layers.

29. (previously presented) The system of claim 16, wherein said fuel flow channels or air flow channels comprise ports that can be opened or closed to selectively activate or deactivate each individual layer of said plurality of layers.

200311582-1

10/686,896

30. (previously presented) The system of claim 16, wherein each of said fuel flow channels is defined along a first axis and each of said cathode air flow channels is defined along a second axis disposed at an angle with said first axis.

31. (original) The system of claim 30, wherein said first axis is substantially normal to said second axis.

32. (previously presented) The system of claim 16, wherein each of said cathode sides comprises a circuit side, wherein said conductors are located on said circuit side.

33. (original) The system of claim 16, wherein said electrolyte seals non-active portions of said substrate.

34. (original) The system of claim 16, further comprising:  
a fuel inlet and an exhaust fluidly coupled to each said fuel flow channel;  
a cathode air inlet and an excess cathode air outlet fluidly coupled to each said cathode air flow channel; and  
seals disposed around said inlets, exhaust and outlet and around a perimeter of said fuel cell array.

35. (original) The system of claim 34, wherein said seals comprise an electrically conductive material.

200311582-1

10/686,896

36. (original) The system of claim 16, wherein said fuel cell layers are coupled so as to form a parallel electrical circuit.

37. (previously presented) The system of claim 24, further comprising a fuel manifold having a plurality of selectively opened inlet ports coupled to said fuel flow plenums disposed within said fuel inlet plenum, and an exhaust manifold having a plurality of selectively opened inlet ports coupled to said fuel flow plenums disposed within said exhaust plenum.

38. (original) The system of claim 37, further comprising a cathode air inlet manifold having a plurality of selectively opened inlet ports coupled to said cathode air flow plenums disposed within said cathode air inlet plenum, and an excess cathode air manifold having a plurality of selectively opened inlet ports coupled to said cathode air flow plenums disposed within said excess cathode air plenum.

39-60. (cancelled)

61. (currently amended) An electrochemical system, comprising:  
means for supporting an array of fuel cells comprising a substrate;  
means defined in a first side of said ~~support means~~ substrate for conveying cathode air across said ~~array of fuel cells~~ of said array; and  
means defined in a second, opposite side of said ~~support means~~ substrate for conveying fuel across said ~~array of fuel cells~~ of said array.

200311582-1

10/686,896

62. (original) The system of claim 61, further comprising means for removing electricity from said array of fuel cells.

63. (original) The system of claim 62, further comprising a plurality of said supporting means.

64. (original) The system of claim 63, wherein said plurality of supporting means comprises means for delivering and removing fuel and cathode air to and from said system.

65. (original) The system of claim 61, wherein said cathode air and said fuel flow in directions substantially normal to each other across cathodes and anodes of said fuel cells respectively.